











# 电容式接近开关 CAPACITANCE PROXIMITY SWITCH

结构分类 Structural category		电容式接近开关 Capacitance proximity switch						
外形编号 Outward Appearance code		CM20	CM34	CM35	CMF37	E2K		
外形图例 Outward appearance illustration								
外形尺寸 Overall dimensions								
检测距离 DETECTION DISTANCE								
埋入式 Flush	直流 DC 6-36 VDC	NPN	NO					
			NC					
			NO+NC					
	交流 AC 90- 250 VAC	PNP	NO					
			NC					
			NO+NC					
	SCR 可控硅 Control- lable silicon	NO						
		NC						
检测距离 DETECTION DISTANCE								
			0-10mm	0-20mm	0-25mm	0-25mm	0-10mm	
非埋入式 Non-Flush	直流 DC 6-36 VDC	NPN	NO	CM20-3010NA	CM34-3020NA	CM35-3025NA	CM37-3025NA	E2K-F10MC1
			NC	CM20-3010NB	CM34-3020NB	CM35-3025NB	CM37-3025NB	E2K-F10MC2
			NO+NC	CM20-3010NC	CM34-3020NC	CM35-3025NC	CM37-3025NC	E2K-F10MC3
	交流 AC 90- 250 VAC	PNP	NO	CM20-3010PA	CM34-3020PA	CM35-3025PA	CM37-3025PA	E2K-F10MF1
			NC	CM20-3010PB	CM34-3020PB	CM35-3025PB	CM37-3025PB	E2K-F10MF2
			NO+NC	CM20-3010PC	CM34-3020PC	CM35-3025PC	CM37-3025PC	E2K-F10MF3
		SCR 可控硅 Control- lable silicon	NO	CM20-2010A	CM34-2020A	CM35-2025A	CM37-2025A	E2K-F10MA0
			NC	CM20-2010B	CM34-2020B	CM35-2025B	CM37-2025B	E2K-F10MAC
	可检测体 Detectable object		导体及介电体 conductor and dielectric body					
消耗电流 Consumption current		直流(NPN PNP)型 DC12V时8mA 24V时15mA、交流型: 10mA以下、DC<15mA、AC<10mA						
输出电流 Output current		直流:200mA, 交流型:300mA						
可输出电压降 Output voltage drop DC/AC		直流(NPN PNP)3V以下, 交流型:7V以下、DC<3V、AC<7V						
响应频率 DC/AC Response frequency		直流(NPN-PNP) 50Hz, 交流型:10Hz						
外壳材料 Shell material		ABS树脂 Resin	ABS塑料 Plastic	ABS塑料 Plastic	ABS塑料 Plastic	ABS塑料 Plastic		
工作环境温度 Working environment temperature		-25°C~70°C						
绝缘电阻 Insulation resistance		50MΩ						
防护等级 Protection grade		IEC标准IP54 IEC standard IP54						
可替代国内型号 Aiyemative model at home and abroad			E2K-C25□□					

# 霍尔传感器 HALL SENSOR

简介 Brief Introduction					
<ul style="list-style-type: none"> <li>SM系列霍尔传感器是由电压调整器, 霍尔电压发生器, 差分放大器, 施密特触发器和集电极开路的输出级组成的磁敏传感器, 其输入为磁感应强度、输出是一个数字电压讯号。</li> <li>SM series Hall sensor is a kind of magnct-sensitive scnsor consisting of voltage regulator, Hall voltage generator, differential amplifier, Schmidt trigger and the output pole of collector open circuit. Its input is the magnetic flux density. The output is adigital voltage signal.</li> </ul>					
特点 Features					
<ul style="list-style-type: none"> <li>电源电压范围宽</li> <li>频率高</li> <li>寿命长, 体积小, 安装方便</li> <li>能直接和晶体管及TTL.MOS等逻辑电路接口</li> <li>Wide mains voltage range</li> <li>High frequency</li> <li>Long service life, compact volume, and convenient installation</li> <li>Directly connect to transistor and logic circuit pore like, TTL.MOS</li> </ul>					
型号及参数 Model and parameters					
外形编号 Outward Appearance code		SM8	SM12	SM14	SM18
外形图例 Outward appearance illustration					
外形尺寸 Overall dimensions					
检测距离 Detection distance		10mm	10mm	10mm	10mm
电源电压 Mains voltage		5~24VDC	5~24VDC	5~24VDC	5~24VDC
可检测物体 Detectable object		永磁体 Permanent magnet	永磁体 Permanent magnet	永磁体 Permanent magnet	永磁体 Permanent magnet
输出低电平电压 Output low level voltage		200mV	200mV	200mV	200mV
输出高电平电流 Output high level current		0.1uA	0.1uA	0.1uA	0.1uA
电源电流 Mains current		8mA	8mA	8mA	8mA
开关频率 ON-OFF frequency		320KHz			
工作点磁强度 Working point magnetic density		22mT			
外壳材料 Shell materia		金属 Metal			
环境温度 Ambient temperature		-25°C~70°C			
防护等度 Protection structure		IEC标准 IP67 standard IP67			
具备型号 Model available	NPN	SM8-31010NA	SM12-31010NA	SM14-31010NA	SM18-31010NA
	NO				
	PNP NO	SM8-31010PA	SM12-31010PA	SM14-31010PA	SM18-31010PA
	PNP NC		SM12-31010NB	SM14-31010NB	SM18-31010NB
	PNP NC		SM12-31010PB	SM14-31010PB	SM18-31010PB